



SHIELDED TYPE

CDRH4D28

Outline

SMT type power inductors whereby the electrode is attached to the ferrite core directly. They are also magnetically shielded to prevent noise radiation.

Dimensions (mm)

LAND PATTERNS(mm)

CONSTRUCTION


(1.2 μ H – 180 μ H)

◆ TYPE CDRH4D28

Parts No.	Inductance	D.C.R. (Ω) (Max) Typical / Rated D. C. Current (A)	Parts No.	Inductance	D.C.R. (Ω) (Max) Typical / Rated D. C. Current (A)
1R0	1.0 μ H		7R4	7.4 μ H	
1R2	1.2 μ H	23.6m (17.5m) / 2.56	8R2	8.2 μ H	117.5m (87.0m) / 1.04
1R5	1.5 μ H		8R6	8.6 μ H	
1R8	1.8 μ H	27.5m (20.4m) / 2.20	8R7	8.7 μ H	
2R2	2.2 μ H	31.3m (23.2m) / 2.04	8R9	8.9 μ H	
2R6	2.6 μ H		100	10 μ H	128.3m (95.0m) / 1.00
2R7	2.7 μ H	43.3m (32.1m) / 1.60	120	12 μ H	131.6m (97.5m) / 0.84
3R0	3.0 μ H		150	15 μ H	149.0m (110.4m) / 0.76
3R3	3.3 μ H	49.2m (36.4m) / 1.57	180	18 μ H	166.0m (123.0m) / 0.72
3R9	3.9 μ H	64.8m (48.0m) / 1.44	220	22 μ H	235.0m (174.5m) / 0.70
4R1	4.1 μ H		270	27 μ H	261.0m (193.3m) / 0.58
4R2	4.2 μ H		330	33 μ H	378.0m (280.0m) / 0.56
4R7	4.7 μ H	72.0m (56.3m) / 1.32	390	39 μ H	383.7m (284.2m) / 0.50
5R0	5.0 μ H		470	47 μ H	587.0m (435.0m) / 0.48
5R3	5.3 μ H		560	56 μ H	624.5m (462.6m) / 0.41
5R4	5.4 μ H		680	68 μ H	699.0m (517.8m) / 0.35
5R6	5.6 μ H	100.9m (74.7m) / 1.17	820	82 μ H	914.8m (677.6m) / 0.32
6R0	6.0 μ H		101	100 μ H	1.02 (765.8m) / 0.29
6R2	6.2 μ H		121	120 μ H	1.27 (976.8m) / 0.27
6R8	6.8 μ H	108.9m (80.7m) / 1.12	151	150 μ H	1.35 (1.08) / 0.24
7R3	7.3 μ H		181	180 μ H	1.54 (1.23) / 0.22

Measuring Freq. (L)

CDRH4D28 100kHz

Tolerance of Inductance

CDRH4D28 \pm 30% (N)

Rated D.C. Current

This indicates the value of current when the inductance is 75%(65%) more than its nominal value and temperature rising $t=40^{\circ}\text{C}$ lower at D.C. superimposition.

Sales Contact

North America
1701 Golf Road, Tower 3
Suite 400, Rolling
Meadows, IL 60008, USA
Tel: (1) 847 545-6700
Fax: (1) 847 545-6720

Japan
Nihonbashi- ingyocho
2-Chome, Chuo-ku,
Tokyo, Japan
Tel: (81) 03 3667-3301
Fax: (81) 03 3667-3456

Hong Kong
14/F, Eastern Centre,
1065 King's Road, Quarry
Road, Hong Kong
Tel: (852) 2880-6688
Fax: (852) 2880-9596

Taiwan
No. 171, Futech Street,
Hsin-I, Taipei, Taiwan,
ROC
Tel: (886) 2 2726-2177
Fax: (886) 2 2728-2726

Singapore
996 Bendemeer
Road #04-05 to 06
Singapore 339944
Tel: (65) 2963-388
Fax: (65) 2963-390

Europe
Chaussee de Tervuren113A,
1160 Brussels
Belgium
Email:
europe.sales@hk.sumida.com